



CODOS 90° RADIO CORTO

NW	STANDARD				NW	XS			
	Ø Ext. (mm) D	Espesor (mm) S	Radio A	Peso Aprox. kgs.		Ø Ext. (mm) D	Espesor (mm) S	Radio A	Peso Aprox. kgs.
1"	33,5	3,38	25,4	0,104	1 1/2"	48,3	5,08	38,1	0,300
1 1/4"	42,2	3,56	31,7	0,172	2"	60,3	5,54	50,8	0,620
1 1/2"	48,3	3,68	38,1	0,249	2 1/2"	73,1	7,01	63,5	1,190
2"	60,3	3,91	50,8	0,449	3"	88,9	7,62	76,2	1,500
2 1/2"	73,1	5,16	63,5	0,875	4"	114,3	8,56	101,6	3,710
3"	88,9	5,49	76,2	1,380	5"	141,3	9,53	127,0	6,800
3 1/2"	101,6	5,74	88,9	1,930	6"	168,3	10,97	152,4	10,580
4"	114,3	6,02	101,6	2,620	8"	219,1	12,70	203,2	21,610
5"	141,3	6,55	127,0	4,420	10"	273,0	12,70	254,0	33,060
6"	168,3	7,11	152,4	6,890	12"	323,1	12,70	304,8	49,600
8"	219,1	8,18	203,2	13,800	14"	355,6	12,70	355,6	66,000
10"	273,0	9,27	254,0	24,500	16"	406,4	12,70	406,4	83,630
12"	323,1	9,53	304,8	36,100	18"	457,0	12,70	457,2	111,000
14"	355,6	9,53	355,6	46,300	20"	508,0	12,70	508,0	136,000
16"	406,4	9,53	406,4	61,200	24"	609,6	12,70	609,6	200,000
18"	457,0	9,53	457,2	77,600					
20"	508,0	9,53	508,0	96,200					
24"	609,6	9,53	609,6	138,300					
30"	762,0	9,53	762,0	217,700					
36"	914,4	9,53	914,4	313,900					
42"	1.066,8	9,53	1.219,2	489,400					

Posibilidad de suministro en 45° y 180°
Bajo consulta otros schedules